1. Replacement toilet seat

One record per toilet. Measure the ceramic bowl. This is not a scale drawing or drilling template. Write UNKNOWN for missing information; use N/A only when a field does not apply.

Location / date / measured by

Toilet brand + full model / existing seat code / photo references

Measured on the toilet

Units: inches / mm (circle one)

A. Fixing-hole centers, left to right

B. Fixing-line midpoint to front outside rim

C. Widest outside bowl width

D. Fixing line back toward tank / obstruction

Mounting access: underneath / concealed / other / UNKNOWN. Describe hardware:

Candidate seat - use the exact drawing and instructions

Seat brand + full model + finish / document revision or URL

Required dimensions / permitted adjustment / unresolved differences

Specified mounting kit / access needed / hardware included?

Before ordering: confirmed match / mismatch / HOLD. Question to resolve:

After fitting according to the manufacturer instructions

Record alignment, intended bumper support, secure fixing, raised-lid and release movement. Stop using a seat that rocks or cannot be secured as instructed.

Date / observed result / next action

Method: Bemis bowl-measurement guidance; product-specific drawing required.

2. Replacement faucet aerator

One record per outlet. Keep measured diameter separate from the confirmed thread. A matching key alone does not identify the part. Use the faucet manufacturer's service instructions.

Location / date / faucet brand + full model

Parts-diagram URL or revision / original replacement code / photo references

Existing outlet

Construction: housing / integrated thread / spray head / other / UNKNOWN

Part markings / which surface was measured / diameter + units

Confirmed FULL thread + male/female of replacement part / evidence

Complete replacement order

Brand + exact part code / assembly or insert only / quantity

Faucet-approved flow + units / stream / evidence

Seal specification + included? / matching service-key code + included?

Old housing and seal condition / unresolved installation requirements

Before ordering: confirmed match / mismatch / HOLD. Question to resolve:

After fitting according to the manufacturer instructions

Inspect the attachment joint and stream. A continuing leak or weak flow remains a separate problem; do not mark the original symptom resolved merely because a new part was fitted.

Date / joint dry? / stream / original symptom / next action

Method: Neoperl construction and replacement guidance. Full references in the article.